



# Conveyor Maintenance and Repair

30 Nov 2020 / SafetyCulture Staff

Complete

Score	0%	Failed items	0	Actions	0
Conducted on				30th Nov, 2020 12:00 PM +08	
Prepared by				SafetyCulture Staff	
Location					

## Inspection

### Roller Maintenance

Does removing, replacing, one person? or transporting the roller require more than one person?

Yes

Does the weight of the roller exceed 50 lb?

Yes

Is the roller difficult to bring close to the body because of its size, bulk, shape?

No

Do employees have to stand on or walk across the conveyor belt to remove or replace the roller?

Yes

To remove the roller, must employees stand on an area more than 4 above ground level?

Yes

Is the footing unsafe? For example, are the floors slippery, inclined, or uneven?

No

Does removing or replacing the roller require fast movements to avoid being pinned or struck by the roller?

Yes

Does removing or replacing the roller require stressful body postures, such as bending to the floor, twisting, reaching overhead, or bending to the side?

No

Is the employee in a kneeling or squatting posture to remove or replace the roller?

Yes

Does the employee lie down to remove or replace the roller?

Yes

Are pry bars used to remove or replace the roller?

No

Is a cutting via torch required to remove or replace the roller?

Yes

Are tools (excluding pry bars and hammers) used to remove or replace rollers?

Yes

Do employees wear gloves when removing or replacing rollers?

Yes

Should employees wear gloves when removing or replacing rollers?

Yes

### Completion

Name and Signature